



High-Density Data Centers Connections



We Create, We Customize, We Connect

TECHNOLOGIES

Providing engineering excellence, connecting you and beyond.

SANWA Technologies Co., Ltd. (formerly Sanwa Denki Kogyo Co., Ltd.) was established in 1947 and has since become a renowned manufacturer of communication and connectivity solutions, specializing in the global optical communications market. With over 75 years of innovation and engineering excellence, SANWA has developed and manufactured high-quality connectivity solutions and components to enhance the performance of optical networks both today and for the future.

Manufacturers designing products since 1947.

SANWA specializes in optical solutions that serve a broad range of international customers within the Telecom, Enterprise, Datacom, Premise wiring, CATV, OEM, Utility, Municipality, Security, and Aerospace/Military markets. With over 40 years of experience in fiber optic components and passive assembly manufacturing, we offer a variety of products and custom solutions tailored to your needs.

Our Vision

For over 75 years, SANWA has sought to establish relationships that are beyond transactional. Diligently collaborating on both custom and standard products with expeditious local support. Over time, we have transformed the traditional Japanese manufacturing philosophy, Monozukuri, exemplified in our everyday pursuit of manufacturing thoughtfulness, and equally focus on all aspects of product delivery: quality, time, and service.

ADVANCING TOGETHER, FORGING THE FUTURE

At SANWA Technologies, we take great pride in our world-class manufacturing facilities that empower us to deliver highquality products to our valued customers.

With two state-of-the-art factories, strategically located in Tokyo, Japan, and Ayutthaya, Thailand, we strive for excellence through cutting-edge technology, precision engineering, and a dedicated focus on quality. Each facility serves a unique purpose, allowing us to meet the diverse needs of our global clientele.

Japan Hachioji Factory: Leading Innovation and Research

Our Hachioji factory, nestled in the western part of Tokyo, is the epitome of innovation and research. Equipped with the latest advancements in manufacturing technology, this facility drives our relentless pursuit of excellence. Our team of seasoned experts leads research and product development, ensuring that SANWA Technologies remains at the forefront of industry advancements. The factory also houses a robust QA, QC, and General Qualification Lab, where every product undergoes stringent testing to meet the highest quality standards. With a focus on low-volume and BCP production, as well as automated MT production and active device production, our Hachioji factory is a hub of progress and ingenuity.

Thailand Ayutthaya Factory: Powering High-Volume Production

Nestled in Ayutthaya, Thailand, our second manufacturing facility is a powerhouse dedicated to high-volume production. With a sharp focus on efficiency and precision, this factory houses cutting-edge equipment for high-volume injection molding and precision assembly and testing. Quality is paramount, and our dedicated QA and QC Lab ensures that each product meets our stringent quality guidelines. We also prioritize tooling maintenance and repair, guaranteeing optimal performance and precision throughout the manufacturing process. For critical processes that demand a controlled environment, our Thailand factory boasts a semi-clean room, enabling us to deliver products with unparalleled purity and accuracy.







LC-UPC/APC UNIBODY

| CONNEG | CTOR |
|--------|------|
|--------|------|

.

.....

.

| and the second | DD |
|----------------|----|
| ~ | |

SEOLUEZZOU UN

| | CODE | | TYPE | | FERRULE I.D. | | | HOUSING | | BOOT | | T COLOR |
|---|----------|-------------------|------|----------|--------------|-------------------|---|---------|---|-------|---|---------|
| (| CN-LCUE | Elite Unibody UPC | SX | Simplex | 125 | SM 125µm | 1 | Blue | 1 | 900µm | 1 | Blue |
| (| CN-LCUAE | Elite Unibody APC | DX | Duplex | 125L | SM 125µm Low Loss | 3 | Green | 2 | 2.0mm | 2 | Black |
| (| CN-LCU | Unibody UPC | | | 1255 | SM 125.5µm | 4 | 4 Beige | | 3.0mm | 4 | Beige |
| (| CN-LCUA | Unibody APC | 1 | | 126 | SM 126µm | | | | | 8 | White |
| | | | 127 | MM 127µm | | | | | | | | |

LC CONNECTOR STANDARD MULTIPIECE

De Davis

| | CODE | | TYPE | FERRULE I.D. | | HO | USING | | BOOT | BOC | T COLOR |
|----------|--------------------------------|----|---------|-----------------|----------------|-------|------------------|-------------------|----------------|-------|---------|
| CN-LCPA | Preassembled | SX | Simplex | 125 | 125µm | 1 | Blue | 1 | 900µm | 1 | Blue |
| CN-LCUK | Unassembled | DX | Duplex | 125L | 125µm Low Loss | 2 | Black | 2 | 2.0mm Standard | 2 | Black |
| CN-LCAPA | LCAPA APC Preassembled | | 1255 | 125.5µm | 3 | Green | 2B | 2mm Bendable Boot | 3 | Green | |
| CN-LCAUK | CAUK APC Unassembled 126 126µm | | 126µm | 4 | Beige | 4 | 2.0mm short 19mm | 4 | Beige | | |
| | | | | 127 | 127µm | 5 | Aqua | 6 | 3.0mm Standard | 5 | Aqua |
| | | | 000 | No Ferrule Opt. | | | | | 8 | White | |

LC-M CONNECTOR



| | CODE | TYPE | | | FERRULE I.D. | HOUSING | | BOOT | | BOOT COLO | |
|-----------------------------|----------------|------|---------|--------------|-------------------|---------|---------|------|-------|-----------|-------|
| CN-LCMPAE | Elite LC-M | SX | Simplex | 125 | SM 125µm | 1 | 1 Blue | | 900µm | 1 | Blue |
| CN-LCMPAAE | Elite LC-M APC | DX | Duplex | 125L | SM 125µm Low Loss | 3 | 3 Green | | 1.2mm | 2 | Black |
| CN-LCMPA | Pre-Assembled | | | 1255 | SM 125.5µm | 4 | Beige | 2 | 2.0mm | 3 | Green |
| CN-LCMUK | Unassembled |] | | 126 | SM 126µm | | | 6 | 3.0mm | 4 | Beige |
| CN-LCMPAA Pre-Assembled APC | | | | 127 MM 127µm | | | | | | 8 | White |
| CN-LCMUKA Unassembled APC | | | | 000 | No Ferrule Opt. | | | | | | |

LC UNIBOOT ROLL OVER CONNECTOR PRE-ASSEMBLED



| | CODE | FERI | RULE I.D. | HOUSING | | BOOT | | | 300T |
|-------------|--------------------------------|--------|------------|---------|----------------|------|-------|---|-------|
| SLCUT-2PHPR | LC Uniboot Roll Over Connector | 1255SM | SM 125.5um | BL | Blue | 20 | 2.0mm | 8 | White |
| | | 127MM | MM 127um | GR | Green | 30 | 3.0mm | | |
| | | | | AQ | Aqua | 50 | 5.0mm | | |
| | | | | ΗV | Heather Violet | | | | |
| | | | | LG | Lime Green | | | | |
| | | | | | | | | | |





SANWA Technologies, Inc.

www.sanwa-tech.com

Americas Sales-MA

sales@snwtech.com Europe Sales





COLOR

T Transparent


COLOR

Black MM

2

MEA Sales

| LC PUSH-PULL |
|--------------|
| UNIBOOT |
| CONNECTOR |



| | CODE | FEI | RRULE I.D. | | HOUSING | BOOT | | BOOT COLOR | | | TAB | |
|--------------|----------------------|------|------------|----|----------------|------|-------|------------|-------|----|--------|--|
| SLCUPL-2PHPR | LC Push-Pull Uniboot | 1255 | SM 125.5µm | BL | Blue | 20 | 2.0mm | - | White | - | No tab | |
| | | 127 | MM 127µm | GR | Green | 30 | 3.0mm | | | T5 | 50mm | |
| | | | | AQ | Aqua | | | | | | | |
| | | | | HV | Heather Violet | | | | | | | |
| | | | | LG | Lime Green | | | | | | | |
| | | | | | | | | | | | | |

| LC P | PM (| CON | INEC | TOR |
|------|------|-----|------|-----|
| | | | | |



| | CODE | FER | RULE I.D. | HO | USING | BC |)OT | BOOT COLOR | | |
|----------|---------------|----------------------|-------------|----|-------|------|-------|------------|-------|--|
| SLC-PHPR | Pre-Assembled | 1255SM SM 125.5um BL | | | Blue | 09P1 | 900µm | GR | Green | |
| | | 1255AP | APC 125.5um | GR | Green | 20P1 | 2.0mm | - | White | |
| | | | | | | 30P1 | 3.0mm | | | |

CODE

LC Simplex to Duplex Converter Clip S Specify

FIBER

900µm Fiber

9

CN-LCMINIDXCLP LC Mini Duplex Clip

CONNECTOR TYPE

AA

ΒB

LC/UPC

LC/APC

CN-LCDXCLP-T

SPECIALTY CLIPS HIGH DENSITY LC SOLUTION





MODULES





| SANWA Technologies | s, Inc. |
|--------------------|---------|
| Americas Sales-CA | Amerio |

CODE


LB-LCK

TYPE

MM Multimode

Singlemode

SM



Interconnect-SNW-Rev 3.0 - Changes without prior notice



LC ADAPTER STANDARD



CODE

TYPE

COLOR

SLEEVE TYPE

| JIANDARD | | CODE | | IYPE | | COLOR | | | SLEEVE TYP | Έ | | | |
|---|-------|--------------|---------|-------------|--------|----------------|---------|------------|---------------|-------------------|-----------|----|--------------|
| | | AD-LC | SX | Simple: | (| 1 Blue | 1 | Zirconia | Ceramic | | | | |
| 10 | | | D> | Duplex | | 2 Black | 2 | Phospho | or Bronze | | | | |
| | | | | | | 3 Green | 3 | Elite Zirc | . Ceramic (L | lltra Low Loss) | | | |
| | | | | | | 4 Beige | | | | | _ | | |
| | | | | | | 5 Aqua | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| LC ADAPTER | | | | | | | | | | | | | |
| SC FOOTPRINT | | | | | | | | | | | | | |
| SNR/JUN | | CODE | | TYPE | | CO | OR | | SL | EEVE TYPE | | | FLANGE |
| ••• | | AD-LC | DXS | J Duplex | | 1 Blue | | 1 | Zirconia Ce | eramic | | FL | With Flange |
| | | | QDS | J Quad | | 2 Black | | 2 | Phosphor E | Bronze | | NF | No Flange |
| 10 | | | | | | 3 Green | | 3 | Elite Zirc. C | Ceramic (Ultra Lo | w Loss) | | |
| 1. 11. | | | | | | 4 Beige | | | | | , | | |
| and the second | | | | | | 5 Aqua | | | | | | | |
| | | | | | | CL F4M T | ranspa | rent | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| LC ADAPTER | | | | | | | | | | | | | |
| MULTIPORT | | CODE | | TYPE | | COLOF | | | VE TYPE | | | | |
| | | SLC | 6AS | P 6 Port | S | BL Blue | | ZR Zircon | ia Ceramic | | | | |
| | | | | | | BK Black | | | | | | | |
| 111. 1111 | | | | | | GR Green | | | | | | | |
| 11. 11 | | | | | | BE Beige | : | | | | | | |
| | | | | | | AQ Aqua | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| LC STACKABLE | | | | | | | | | | | | | |
| CEDIEC | | CODE | т | YPE | | COLOR | | #PORTS | | #ROWS | | | |
| | | | | | 4 | | NC | 1 | | | | | |
| A CONTRACT OF A CONTRACT. | | AD-STKLC | | Angled | 1 | Blue | N6 | 6 Ports | M1 | 1 Row | | | |
| 111. 111 | | | ST | Straight | 3 | Green | N8 | 8 Ports | M2 | | | | |
| | 11.10 | | | | 4 | Beige | N12 | 12 Ports | M3 | | | | |
| Carlin . | 1 | | | | 5 | Aqua | N | ~ Ports | S | Specify | | | |
| in in it | 5 | | | | HV | Heather Violet | N24 | 24 Ports | | Â | 4 | | |
| | | | | | | | S | Specify | | | | 10 | |
| | | | | | | | | | | · | | 2. | |
| | | | | | | | | | | | 5 | K | l |
| | | | | | | | | | | | | | |
| | sanw | A Technolog | gies, l | nc. | ww | w.sanwa-tech.c | om | sales | @snwtech.co | om | | | |
| | | cas Sales-CA | | Americas Sa | les-TX | Americ | as Sale | | Europe | | MEA Sale: | s | Asia Sales |
| | , | | , | | // | / 4110110 | | | 201006 | | | - | , 1810 00103 |
| | | | | | | | | | | | | | |

CODE

CODE

SLC

TYPE

TYPE

2A Duplex

HOUSING

HOUSING

SLEEVE TYPE

SLEEVE TYPE

45M Metal ZR Zirconia Ceramic



INTERNAL SHUTTER

With Shutter

No Shutter

INTERNAL SHUTTER

SH

В

.




LC 45 DEGREE EMI SHIELDING ADAPTER



ALL-IN-ONE LC ADAPTER



LC SNUG FIT



| SLC | 2ASP | Duplex | BL | Blue | ZR | Zirconia Ceramic | SSH2 | With Shutter | |
|-----|------|--------|----|----------------|----|------------------|------|--------------|--|
| | 4ASP | Quad | GR | Green | | | | | |
| | | | AQ | Aqua | | | | | |
| | | | HV | Heather Violet | | | | | |
| | | | LG | Lime Green | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |

| CODE | | TYPE | COLOR | | SLEEVE TYPE | | | |
|---------|----|------------|-------------------|--|---|--|--|--|
| AD-LCSF | DX | Duplex | 1 | Blue | 1 | Zirconia Ceramic | | |
| | QD | Quad | 2 | Black | 2 | Phosphor Bronze | | |
| | | | 3 | Green | 3 | Elite Zirc. Ceramic (Ultra Low Loss) | | |
| | | | 4 | Beige | | | - | |
| | | | 5 | Aqua | | | | |
| | | AD-LCSF DX | AD-LCSF DX Duplex | AD-LCSF DX Duplex 1 QD Quad 2 3 4 | AD-LCSF DX Duplex 1 Blue QD Quad 2 Black 3 Green 4 Beige | AD-LCSF DX Duplex 1 Blue 1 QD Quad 2 Black 2 3 Green 3 4 Beige | AD-LCSF DX Duplex 1 Blue 1 Zirconia Ceramic QD Quad 2 Black 2 Phosphor Bronze 3 Green 3 Elite Zirc. Ceramic (Ultra Low Loss) 4 Beige | |

Interconnect-SNW-Rev 3.0 - Changes without prior notice

SANWA Technologies, Inc. Americas Sales-CA

www.sanwa-tech.com Americas Sales-TX

sales@snwtech.com

Europe Sales





Asia Sales



5



| Ŵ | | | | | | | | | | | |
|-------------|-------------|---------|------|--------------|----------|------|----------|----------------|--------|-------------------|------|
| ñ | ATTENUATORS | | CODE | | | | TYPE | CONNECTOR TYPE | | ATTENUATION LEVEL | |
| | | AT | Dope | d Fiber Atte | enuators | 1 | Standard | LC | LC UPC | 01 | 1dB |
| | | | | | | 2 | Special | LCA | LC APC | 03 | 3dB |
| | S | | | | | S | Specify | | | 04 | 4dB |
| RS RS | | | | | | | | | | 05 | 5dB |
| TERMINATORS | Nº 14 | | | | | | | | | 07 | 7dB |
| AATO | 4 | | | | | | | | | 08 | 8dB |
| | | | | | | | | | | 09 | 9dB |
| ER 1 | TERMINATORS | PRO | DUCT | CON | INECTOR | ΓΥΡΕ | | | | 10 | 10dB |
| ¥ ﴾ | | Т | M | LC | LC UPC | | | | | 12 | 12dB |
| | | L | | LCA | LC APC | | | | | 15 | 15dB |
| | | | I | - | | | I | | | 20 | 20dB |
| | | | | | | | | | | 25 | 25dB |
| | State 1 | | | | | | | | | 30 | 30dB |

| | SC-LC HYBRID ADAPTER | | [] | | | | | 7 | | | |
|--|-------------------------|---------|--------------|--------|----------|-------|--------|--------------|-----------|-----------|--------|
| | | •••••• | CODE | | - | EEVE | | _ | | | |
| | | | ADH-LCSC | 1 | Zirco | onia | | | | | |
| | A P | | | | | | | | | | |
| | LC-MU HYBRID | | | | | | | | | | |
| | ADAPTER | | CODE | | <u>د</u> | LEEVE | : | | | | |
| | | ••••••• | ADH-LCMU | 1 | 1 | onia | - | - | | | |
| | | | | 2 | - | | Bronze | | | | |
| | LC-MU CONVERSION | | | | | | | | | | |
| notice | PLUG | | CODE | Ξ | | CC | LOR | OPTICAL | FIBER ANI |) WAVELEN | GTH |
| it prior | | ••••• | SCV-LCMU-SN | 1-C | | BL | Blue | SM10/125 | 1.31µm | • 1.55µm | |
| withou | | | SCV-LCMU-50 | /125-0 | С | BE | Beige | GI50/125 1 | .31µm | | |
| hanges | Cal | | SCV-LCMU-62 | .5/125 | 5-C | BE | Beige | GI62.5/125 | 1.31µm | | |
| SNW-Rev 3.0 - Changes without prior notice | 4 | | | | | | | | | | |
| SNW-R. | | SANW | A Technologi | es, Ir | IC. | | www.sc | anwa-tech.cc | m | sales@snv | vtech. |

Interconnect-SNW-Rev 3.0 - Changes without prior notice

| SAN |
|-----|
| A |
| |



| FERRULE | | | INNER DIAMETER | FLANGE | | |
|---------|--------------------------|------|----------------|--------|-----------|---|
| F-MU-S | MU Connectors Singlemode | 125 | 125µm | NF | No Flange | |
| F-LC-S | LC Connectors Singlemode | 1255 | 125.5µm | FL | MU Flange | |
| | | 126 | 126 µm | | | - |


| FERRULE | | | INNER DIAMETER | FLANGE | | |
|---------|-------------------------|-----|----------------|--------|-----------|--|
| F-MU-M | MU Connectors Multimode | 127 | 127µm | NF | No Flange | |
| F-LC-M | LC Connectors Multimode | | | FL | MU Flange | |

| | CODE | | INNER DIAMETER | | LENGTH |] |
|------|-----------------|-----|----------------|----|--------|---|
| S-ZR | Zirconia Sleeve | 125 | 1.25mm | LC | 6.8mm | |

| SMALL | BOOT | | | |
|---------------|--------------------------------|-------|--------|--|
| BOOT CODE | DESCRIPTION | COLOR | | |
| - | | _ | | |
| | LC BOOTS | 1 | Blue | |
| F4M-BTLC9B | 900µm LC Boot | 2 | Black | |
| F4M-BTLCDX9 | 900um LC Boot for DX Connector | 3 | Green | |
| F4M-BTLC12B | 1.2mm LC Boot | 4 | Beige | |
| F4M-BTLC2B | 2.0mm Standard LC Boot | 5 | Aqua | |
| F4M-BTLC19L2R | 2.0mm Round short 19mm LC Boot | 6 | Red | |
| F4M-BTLC3B | 3.0mm Standard LC Boot | 7 | Yellow | |
| F4M-BTLC2BFL | 2.0mm Bendable LC Boot | 8 | White | |
| F4M-BTLC3BFL | 3.0mm Bendable LC Boot | 9 | Gray | |
| F4M-BTLC245D | 45° Angled LC Boot | | | |
| F4M-BTLC290D | 90° Angled LC Boot | | | |

| LC-M | BOOTS (SPECIFIC) |
|-------------|------------------|
| F4M-BTLCM9B | 900um LC-M Boot |
| F4M-BTLCM2B | 2.0mm LC-M Boot |
| F4M-BTLCM3B | 3.0mm LC-M Boot |

Standard LC connectors crimps works with 1.6,1.8 and 2mm cables For LCM and standard LC with short boots is offered the 32mm version



| | LC CRIMP OPTIONS | | | | | | | |
|-------|-------------------|---|------|------------|----------------|--|--|--|
| | HEATSHRINK | C | L | CRIMP SIZE | CRIMP & EYELET | | | |
| | F4M-CRLC2-19-7B | | 19mm | 2.0mm | | | | |
| | F4M-CRLC2-19-8B | | 19mm | 2.011111 | - | | | |
| | F4M-CRLC2-32-7B | | 32mm | 2.0mm | | | | |
| | F4M-CRLC2-32-8B | | 32mm | 2.011111 | - | | | |
| on | F4M-CRLC2-7B | | 42mm | 2.0mm | | | | |
| UII | F4M-CRLC2-8B | | 42mm | 2.000 | - | | | |
| | F4M-CRLC3-7B | | 42mm | 2.0.000 | | | | |
| | F4M-CRLC3-8B | | 42mm | 3.0mm | F4M-CR3LC | | | |
| sales | sales@snwtech.com | | | | | | | |

MEA Sales

| SANWA | Technol | ogies, | Inc. |
|-------|---------|--------|------|
| | | | |

www.sanwa-tech.com

Americas Sales-CA

Americas Sales-TX Americas Sales-MA

Europe Sales

les

Asia Sales



| ſ | |
|---|---|
| ſ | |
| | J |
| | |
| |] |
| - | ╢ |
| U | Ŋ |



ZIRCONIA FERRULES


LC-MU MULTIMODE

ZIRCONIA ADAPTERS SLEEVES





lc boots





 SANWA Technologies, Inc.
 www.sanwa-tech.com
 sales@snwtech.com

 Americas Sales-CA
 Americas Sales-TX
 Americas Sales-MA
 Europe Sales
 MEA

MEA Sales












| LC-M BOO | ts (specific) |
|--------------|-----------------|
| F4M-BTLCM9B | 900um LC-M Boot |
| F4M-BTLCM2B | 2.0mm LC-M Boot |
| F4M-BTLCM12B | 1.2mm LC-M Boot |
| | |







| | BOOT COLOR F4M- BTLCM9B | | |
|----|----------------------------|--|--|
| 1 | Blue | | |
| 2 | Black | | |
| 3 | Green | | |
| 5 | Aqua | | |
| 8 | White | | |
| 11 | Magenta | | |
| | | | |

| BOOT COLOR F4M-BTLCM-2S | | |
|----------------------------|--------|--|
| 1 Blue | | |
| 7 | Yellow | |
| 8 White | | |

| BOOT COLOR F4M-BTLCM12B | | |
|----------------------------|-------|--|
| 1 | Blue | |
| 3 | Green | |
| 8 | White | |







| SMALL FORM FACTOR BOOTS | | |
|-------------------------|--------------------------------|--|
| BOOT CODE DESCRIPTION | | |
| LC BOOTS | | |
| F4M-BTLC9B | 900µm LC Boot | |
| F4M-BTLCDX9 | 900um LC Boot for DX Connector | |
| F4M-BTLC12B | 1.2mm LC Boot | |
| F4M-BTLC2B | 2.0mm Standard LC Boot | |
| F4M-BTLC19L2R | 2.0mm Round short 19mm LC Boot | |
| F4M-BTLC3B | 3.0mm Standard LC Boot | |
| F4M-BTLC2BFL | 2.0mm Bendable LC Boot | |
| F4M-BTLC3BFL | 3.0mm Bendable LC Boot | |
| F4M-BTLC245D | 45° Angled LC Boot | |
| F4M-BTLC290D | 90° Angled LC Boot | |

SANWA TECH Offers a 1.6mm Crimp Ring that is compatible with all 2.0mm boots.

SANWA Technologies, Inc.

Americas Sales-CA

Americas Sales-TX

sales@snwtech.com

Europe Sales

MEA Sales



www.sanwa-tech.com





| | TIA/EIA,IEC& GR-326-CORE | RoHS & REACH | Flammability rating: UL 94V-0 |
|-----------------------------|--------------------------|-------------------------|-------------------------------|
| Push Pull Series Connectors | • | • | • |
| Roll Over Connector | • | • | • |
| Simplex & Duplex Connectors | • | • | • |
| PM Connectors | • | • | • |
| LC Adapter Series | • | • | • |
| Shutters | | • | • |

SANWA's LC Series delivers the highest optical performance with compact innovative engineering and new designs. We use the highest industry standards to meet and exceed our customers' performance expectations. Our talented and dedicated engineering department's ability to design and manufacture new products, as well as customization of existing products truly sets us apart from the competition.

Application

- Datacom and Telecom
- · Medium and long distance optical fiber transmission lines
- · Subscriber's optical fiber transmission lines

OVER THE WORLD

SANWA product selection offers a wide range of high-quality and reliable solutions for various applications. Fiber optic technology is known for its ability to transmit data at incredibly fast speeds over long distances, making it ideal for telecommunications, networking, and data center environments.

USA EUROPE MIDDLE EAST TAIWAN THAILAND JAPAN

www.sanwa-tech.com



SANWA Technologies, Inc.

Americas Sales-CA 9685 Via Excelencia; Suite 106, San Diego, CA 92126 Tel: +1-{858}-397-2585 Fax: +1-{858}-397-2584

Americas Sales-TX 4012 Preston Rd. Plano, TX 75093 Tel: +1 (972)-503-3031 Fax: +1 (972)-503-3032 Americas Sales-MA 287 Turnpike Road Westborough, MA 01581 Tel: +1 (508)-616-9500 Fax: +1 (508)-616-9600 Europe Sales Aleja Armii Krajowej 61, Bud. C, 50-541 Wrocław, PL Tel: +48 71 7277237

Fax: :+48 71 7939911

sales@snwtech.com

MEA Sales

DP A6, 108, Silicon Oasis Free Zone Dubai, United Arab Emirates Tel: +971 4 3344970 Fax: +971 4 3344971 Asia Sales 13F, Changxing Rd., Luzhou Dist., New Taipei City 247, Taiwan (R.O.C.) Tel: +886 939512000 Fax: +886 2 8285450

Catalog 2023

All information provided in this document is subject to legal disclaimers. SANWA Technologies, Inc. © 2023. All rights reserved.

Interconnect-SNW-Rev 3.0 - Changes without prior notice